



Delock Cable Displayport 1.2 male > Displayport male 4K 2 m

Description

This cable enables the connection between devices with a Displayport interface, e.g. monitors or TVs, to a PC or a laptop. Displayport is a standardized universal connecting standard by VESA for the transfer of video and audio signal.



Specification

- Connector:
Displayport 20 pin male >
Displayport 20 pin male
- Displayport 1.2 specification
- Pin 20 not connected
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.3 mm
- Copper conductor
- Triple shielded cable
- Gold-plated connector
- Transfer of audio and video signals
- Data transfer rate up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Colour: black
- Length incl. connector: ca. 2 m

System requirements

- A free Displayport interface

Package content


- Displayport cable

Item No. 83806

EAN: 4043619838066

Country of origin: China

Package: Poly bag



Images





General	
Specification:	Displayport 1.2a
Interface	
Connection 1:	1 x Displayport 20 pin male
Connection 2:	1 x Displayport 20 pin male
Technical characteristics	
Data transfer rate:	21,6 Gb/s
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing:	PVC
Cable diameter:	7.3 mm
Connector finishing:	nickel-plated
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	28 AWG
Shielding:	triple
Colour:	black
Length:	2 m