



## QNAP QSW-L3205-1C4T 4 Managed 10G Ethernet (100/1000/10000) Desktop Black

**Brand :** QNAP

**Product code:** QSW-L3205-1C4T

**Product name :** QSW-L3205-1C4T 4



4 x 10G/5G/2.5G/1G/100M, 1 x 10GbE SFP+/RJ45 Combo Ports, 100Gbps, Desktop, 44 x 210 x 160 mm  
QNAP QSW-L3205-1C4T 4. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 4, Console port: RJ-45. Full duplex. MAC address table: 16000 entries, Switching capacity: 100 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE.... DC input voltage: 12 V. Power connector: DC-in jack. Form factor: Desktop

| Management features                             |                                                                                                                                                                 | Multicast features                |           |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------|
| Switch type *                                   | Managed                                                                                                                                                         | Multicast support                 | ✓         |
| Quality of Service (QoS) support                | ✓                                                                                                                                                               | <b>Design</b>                     |           |
| Web-based management                            | ✓                                                                                                                                                               | Form factor                       | Desktop   |
| System event log                                | ✓                                                                                                                                                               | Product colour                    | Black     |
| <b>Ports &amp; interfaces</b>                   |                                                                                                                                                                 | LED indicators                    | ✓         |
| Basic switching RJ-45 Ethernet ports quantity * | 4                                                                                                                                                               | <b>Power</b>                      |           |
| Basic switching RJ-45 Ethernet ports type *     | 10G Ethernet (100/1000/10000)                                                                                                                                   | Power source *                    | DC        |
| Combo SFP ports quantity                        | 1                                                                                                                                                               | Power supply included *           | ✓         |
| Console port                                    | RJ-45                                                                                                                                                           | DC input voltage                  | 12 V      |
| Power connector                                 | DC-in jack                                                                                                                                                      | Input current                     | 3 A       |
| <b>Network</b>                                  |                                                                                                                                                                 | Power consumption (max)           | 36 W      |
|                                                 |                                                                                                                                                                 | <b>Other features</b>             |           |
| Networking standards *                          | IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Warranty period                   | 2 year(s) |
| 10G support *                                   | ✓                                                                                                                                                               | <b>Operational conditions</b>     |           |
| Port mirroring                                  | ✓                                                                                                                                                               | Operating temperature (T-T)       | 0 - 40 °C |
| Full duplex                                     | ✓                                                                                                                                                               | Operating relative humidity (H-H) | 0 - 90%   |
| Flow control support                            | ✓                                                                                                                                                               | <b>Weight &amp; dimensions</b>    |           |
| Link aggregation                                | ✓                                                                                                                                                               | Width                             | 210 mm    |
| Broadcast storm control                         | ✓                                                                                                                                                               | Depth                             | 160 mm    |
| Ethernet LAN data rates                         | 10,100,1000,10000 Mbit/s                                                                                                                                        | Height                            | 44 mm     |
| Auto-negotiation                                | ✓                                                                                                                                                               | Weight                            | 1.17 kg   |
| VLAN support                                    | ✓                                                                                                                                                               | <b>Packaging content</b>          |           |
| <b>Data transmission</b>                        |                                                                                                                                                                 | User guide                        | ✓         |
| Switching capacity *                            | 100 Gbit/s                                                                                                                                                      | Rack mount kit                    | ✓         |
| Throughput                                      | 50 Gbit/s                                                                                                                                                       | <b>Packaging data</b>             |           |
| MAC address table *                             | 16000 entries                                                                                                                                                   | Package type                      | Box       |
| Static route                                    | ✓                                                                                                                                                               | Package width                     | 328 mm    |
| Jumbo frames support                            | ✓                                                                                                                                                               | Package depth                     | 216 mm    |
|                                                 |                                                                                                                                                                 | Package height                    | 61 mm     |
|                                                 |                                                                                                                                                                 | Package weight                    | 2.71 kg   |
|                                                 |                                                                                                                                                                 | <b>Logistics data</b>             |           |
|                                                 |                                                                                                                                                                 | Country of origin                 | Taiwan    |

| Security        |             | Logistics data                   |         |
|-----------------|-------------|----------------------------------|---------|
| DHCP features   | DHCP client | Products per master (outer) case | 8 pc(s) |
| IGMP snooping   | ✓           |                                  |         |
| Loop protection | ✓           |                                  |         |



4711103086216



0885022028603



885022028603

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.